

CARRYALL 502

Club Car



CARRYALL
ALWAYS TOUGH, ALWAYS READY




The Carryall 502 was expertly designed with your needs in mind. With extra room, and a high-visibility dash, you can now manage and care for your facility without interruption.

CARRYALL 502

WHERE OUR STANDARDS MEET YOURS

The Carryall 502, available with Club Car exclusive Kohler Command Pro® closed-loop EFI engine, combines the features you need most to do your best work with the quality, performance, and engineering of our 500 series. No detail was left out to ensure this vehicle works as intuitively and relentlessly as you do.



- 
Max Speed
19 mph
- 
Max Vehicle Capacity
1200 lbs
- 
Horsepower
14 hp (gas)
3.7 hp (electric)
7.4 hp (Li-ion)

CARRYALL 502



OPTIONS & ACCESSORIES

Ask your Club Car sales representative for details.



High-Visibility Dash enhances sight lines for an unobstructed view. *Optional windshield available



Extra-Wide Monsoon Canopy for fast drainage and better water management.



Spacious Interior means plenty of room for equipment and canine crew members.



Console with Standard Dual USB & Multi-Use Cup Caddy keeps devices charged and drinks, radios, and tools secure.

Available Body Colors

Standard Colors

Premium Colors



White



Dark Green



Bright Blue



Dark Gray



Black



Beige

Colors may vary by product

GASOLINE

ELECTRIC

LITHIUM ION

	GASOLINE	ELECTRIC	LITHIUM ION
ENGINE	Kohler EFI, 4-cycle Gas	48-volt DC 48-volt AC	48-volt 3-phase AC
HORSEPOWER	14.5 hp (10.8 kW) rated @ 3600 RPM per SAE J1940	3.7 hp (2.7 kW) rated; peak 20 hp(14.9 kW)	7.4 hp (5.5 kW) rated @ 2863 rpm; Peak 21.4 hp (16 kW)
BATTERIES	12-volt 500 CCA 105 min reserve	Eight 6-volt flooded lead acid	Std: Vanguard 7.0kWh Lithium Light Duty: Vanguard 4.0kWh Lithium
CHARGER	N/A	On-board DeltaQ QuiQ (1 kW high frequency)	Std: DeltaQ IC650 - 650W high frequency Opt: DeltaQ IC900 - 900W high frequency
STEERING	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion
FRONT SUSPENSION	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks
BRAKES	4-wheel mechanical drum	4-wheel mechanical drum	4-wheel mechanical drum
PARK BRAKE	Foot operated, multi-lock	Foot operated, multi-lock	Foot operated, multi-lock
BODY AND FINISH	ArmorFlex® with automotive paint/clearcoat, aluminum finish	ArmorFlex® with automotive paint/clearcoat, aluminum finish	ArmorFlex® with automotive paint/clearcoat, aluminum finish
TIRES	18 x 8.5-8, 6-ply	18 x 8.5-8, 6-ply	18 x 8.5-8, 6-ply
BED L x W x H	44.2 x 47.5 x 10.5 in (112.2 x 120.6 x 26.6 cm)	44.2 x 47.5 x 10.5 in (112.2 x 120.6 x 26.6 cm)	44.2 x 47.5 x 10.5 in (112.2 x 120.6 x 26.6 cm)
BED CAPACITY	800 lbs (363 kg)	800 lbs (363 kg)	800 lbs (363 kg)
TOTAL PAYLOAD CAPACITY	1200 lbs (544 kg)	1200 lbs (544 kg)	1200 lbs (544 kg)
TOWING CAPACITY	1500 lbs (680 kg)	1500 lbs (680 kg)	1500 lbs (680 kg)
WHEELBASE	78.1 in (198 cm)	78.1 in (198 cm)	78.1 in (198 cm)
GROUND CLEARANCE	4.2 in (10.7 cm)	4.2 in (10.7 cm)	4.2 in (10.7 cm)
FUEL TANK CAPACITY	5.5 gal (20.8 L)	N/A	N/A
CURB WEIGHT	907 lb (411 kg)	1393 lb (632 kg)	938 lb (425.5 kg)
SPEED RANGE	15-17 mph (24-27 km/h)	5-17 mph (8-27 km/h)	5-19 mph (8-31 kph)
LIMITED WARRANTY	3 yr/3000 hr limited powertrain/frame 2 yr limited remaining vehicle	4 yr limited battery 3 yr limited powertrain/frame 2 yr limited remaining vehicle	5 yr limited battery warranty 3 yr limited powertrain/frame 2 yr limited remaining vehicle